



Product Description

| | Series | KVM-19 Series |
|---------------------|-----------------------|--|
| LCD Display | Display Type | XGA TFT LCD |
| | Display Size | 4:3 - 19" (inch) |
| | Visual Area (MM) | 386,4 (H) x 289,8 (V) |
| | Resolution | 1600*1200 |
| | Display Color | 16,7 M |
| | Luminosity | 300 (cd/m ²) |
| | Contrast | 1000:01:00 |
| | Pixel Internal | 0,242 (H) x 0,242 (W) |
| | Operating Life | LCD MTBF>50000H, Backlight MBTF>30000H |
| | Power Supply | 25W |
| | Keyboard Design | 104 Keys |
| | Compatibility | IMB/AT, Support Microsoft Windows 9X / Me / nt / 2K / XP |
| Keyboard | Keyboard Connect Port | PS/2 and USB |
| | Operating Life | >1.000.000 times |
| | Hardware Port | PS/2 and USB |
| Touch Pad | Operating System | Support Microsoft Windows 9X / Me / nt / 2K / XP |
| | Life Time | Above 1.000.000 |
| Power Supply | | DC 12V 4A 48W |
| Color | | Black Roast Paint or Industrial Gra (Optional) |
| Material | | Electrolysis Steel Panel / Al-alloy |
| N.W / G.W | | 16 kg / 23,5 kg |
| Size (WxDxH) - (MM) | | 480 x 609,2 x 44 |
| Installation Depth | | 600mm - 810 mm (Selecting the Right Hook) |
| Operating Temp | | 0 - 60°C |
| Storage Temp | | 20 - 65°C |
| Port | | 8 port Computer Connection |