

Comply and compatible with 19 inch international standard, metric system and ETSI standard. Reliable structure and static loading achieves to 800 kg.


High density vented hole front and rear door, with international popular tempered glass front door.



Front View


Product Description

Product Type	Glass Door Close Rack
Product ID	IR9027G
Size	27U
Weight	± 92 kg
Dimension (DxWxH)	900 x 600 x 1320 mm
Complete Set with	<ul style="list-style-type: none"> • Glass Front Door, Steel Rear Door and 2 Side Door with lock • 1 Unit Horizontal PDU 8 outlet with switch • 1 Unit Bracket Fan Modular with 2 Fan • 1 pc Fixed Shelf • 1 pc Top Brush Panel • 1 set Cable Ring • 1 set Adjustable Foot of 4 • 1 set Castor of 4 • 50 set Cagenuts & Screws

Product Drawing


1. Top Panel
2. Fan Tray
3. Frame
4. Rear Door
5. Front Door
6. Shelf
7. Bottom Panel
8. Side Door
9. Mounting Angle
10. Mounting Profile

The side door easy to be installed & uninstalled quickly which make the working conveniently. Include castor & adjustable feet which make the moving and fixing easily.

Comfortable handle with safe lock front and rear door lock system enlarges the security.



Side View



Back View



Product Drawing

